

LABELING APPARATUS

Publication number: WO2005073092 (A1)

Publication date: 2005-08-11

Inventor(s): YUYAMA SHOJI [JP]; YOSHINA KATSUNORI [JP]

Applicant(s): YUYAMA MFG CO LTD [JP]; YUYAMA SHOJI [JP];
YOSHINA KATSUNORI [JP]

Classification:


- **international:** **B65C3/12; B65C3/16; B65C9/32; B65C3/00; B65C9/26;**
(IPC1-7): B65C3/08


- **European:** B65C9/32; B65C3/16

Application number: WO2005JP00658 20050120


Priority number(s): JP20040024669 20040130


Also published as:

 US2007163717 (A1)

 JP2005212878 (A)


Cited documents:

 JP2001130504 (A)

 JP54002558B (B)

Abstract of **WO 2005073092 (A1)**

A labeling apparatus, comprising at least three support rollers (156a) to (156c) rotating in contact with the outer peripheral surface of a vial bottle (3), arms (155a) and (155b) rotatably supporting the support rollers (156a) to (156c), a rotating means (rotating rollers (210a) and (210b)) rotating the vial bottle (3) rotatably held by the support rollers (156a) to (156c), a label supply means (200) supplying a label (4) stuck on the outer peripheral surface of the vial bottle (3), and an endless member (157) rotating between the first support roller (156a) first coming into contact with the label (4) delivered from the label supply means (200) and the second support roller (156b) next coming into contact with the label (4) according to the rotation of the vial bottle (3).



Data supplied from the **esp@cenet** database — Worldwide